

## P/N : 48 MMC SCS

UPC SC simplex multimode connector for 900µm/2mm/3mm cables



P/N: 48MMCSCS

SC UPC simplex connector, suitable for OM1, OM2, OM3, OM4

## Applications

MMC optical connectors are ideal for all multimode applications. These connectors are a part of the complete optical link and suit all types of multimode networks, like Telecom, LAN (local Area Network), WAN (Wide Area Network) and MAN (Metropolitan Area Network). They can be assembled thanks to the MMC MASTER heat cure tool kit, or either any other cold cure tool kit.

## General Characteristics

- Optically and mechanically compatible with all the equivalent adapters.
- Multimode connector with ceramic ferrule (ZrO<sub>2</sub>) and beige composite body
- 900µm, 2mm & 3mm black boots included
- Crimp termination
- Packaging : pack of 6 units

## Standards compliance

- IEC 60874-14,
- CECC BFOC 86260
- Bellcore/Telcordia
- TIA/EIA 604-3, TIA/EIA 568
- With no hazardous substances as detailed in ROHS 2002/95/EC

## P/N : 48 MMC SCS

UPC SC simplex multimode connector for 900µm/2mm/3mm cables

### Physical Properties

Types	SC
Surface of the ferrule	Ultra Polished
Outside diameter of the ferrule	2.5mm +/- 0.001mm
Material of ferrule	ZrO <sub>2</sub> (Zirconia / Ceramic)
Connector surface	Convex
Connection of fiber	Epoxy
Material of body	Composite, beige housing
Ferrule drilling	125/126 µm
Type of boots	900µm, 2mm & 3mm
Colour of boots	black
Insertion method	Push-pull

### Optical performances

Mating cycles:	> 1000 cycles. After 2000, typical increase of 0.05 dB
Return Loss	> 25.0 dB
Insertion Loss (Attenuation)	< 0.20 dB
Variations at low temperature (-10°C during 4 days)	< 0.3 dB
Variations at high temperature (60°C during 4 days)	< 0.3 dB
Variations at high humidity (90 à 95% @ 40°C during 4 days)	< 0.3 dB
Operating temperature range	-40°C to 80°C
Storage temperature range	-40°C to 90°C

### Related products

Part number	Description	Packaging
48 MMT SCS	UPC Multimode simplex SC adapter	Pack of 6
48 MMT SCD	UPC Multimode duplex SC adapter	Pack of 6
MMC MASTER	Optical tool case	Unit



48MMTSCS



MMC MASTER



48MMTSCD

### Ordering information

Part number	Description	Packaging
48 MMC SCS	UPC Multimode simplex SC connector	Pack of 6